

Material Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

U.S. Department of Labor
 Occupational Safety and Health Administration
 (Non-Mandatory Form)
 Form Approved
 OMB No. 1218-0072

IDENTITY (As used on Label and List) COLOR MOMENT (Standard/Rainbow colors)	Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.
---	---

Section I

Manufacturer's Name: King Research, Inc.	Emergency Telephone Number: (800) 424-9300
Address: 114 - 12 th Street	Telephone Number for Information: (718) 788-0122
Brooklyn, NY 11215	Date Prepared: November 17, 2004
	Signature of Preparer (optional)

Section II – Hazardous Ingredients/Identity information

Hazardous Components (Specific Chemical Identity; Common Names(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
Ethyl Alcohol	CAS #64-17-5	N/E	1100 ppm TWA	N/E
Isobutane	CAS #75-28-5	N/E		N/E
Propane	CAS #74-98-6	N/E	850 ppm TWA	N/E

Section III – Physical/Chemical Characteristics

Boiling Point:	N/A	Specific Gravity (H2O = 1)	N/A
Vapor Pressure (mm Hg.)	45 PSIG	Melting Point:	N/A
Vapor Density (AIR = 1)	N/A	Evaporation Rate (Butyl Acetate =1)	N/A
Solubility in Water: Not soluble			
Appearance and Odor: When sprayed, colored quick-drying liquid, pleasant odor			

Section IV – Fire and Explosion Hazard Data

Flash Point (method used): N/A	Flammable Limits: N/A	LEL N/D	UEL N/D
Extinguishing Media: CO ₂ , Water			
Special Fire Fighting Procedures: Wear positive pressure, self-contained breathing apparatus.			

Unusual Fire and Explosion Hazards: Do not expose to heat or store at temperatures above 120° F (49° C)

